



	Panther, 812 (LRV - 2.94)		Lupus Grey, 811 (LRV - 5.32)	<table border="0"> <tr> <td>Style</td> <td>Tufted 1/10" Gauge Loop Pile Tile</td> </tr> <tr> <td>Yarn Construction</td> <td>100% Solution Dyed Nylon</td> </tr> <tr> <td>Pile Yarn Weight</td> <td>500gsm</td> </tr> <tr> <td>Pile Height</td> <td>3mm</td> </tr> <tr> <td>Total Weight</td> <td>4280gsm</td> </tr> <tr> <td>Total Thickness</td> <td>5.5mm</td> </tr> <tr> <td>Backing</td> <td>100% Envirobac - minimum of 75% recycled material</td> </tr> <tr> <td>Additional Backing</td> <td>Komfort Bac available on request</td> </tr> <tr> <td>Tile Size</td> <td>50cm x 50cm</td> </tr> <tr> <td>Tiles Per Box</td> <td>20 (5m²)</td> </tr> <tr> <td>Wear Classification</td> <td>Heavy Contract Class 33</td> </tr> <tr> <td>Luxury Class</td> <td>LC1</td> </tr> <tr> <td>Anti-static</td> <td>Suitable for use with computers. Less than 2Kv</td> </tr> <tr> <td>Colour Fastness</td> <td>Light (BS EN ISO 105:B02) >6 Shampoo (BS 1006:UK-TB:1990) 4-5 Dry Rubbing (BS EN ISO 105:B01) 4-5 Wet Rubbing (BS EN ISO 105:X12) 4-5</td> </tr> <tr> <td>Flammability</td> <td>BS5287 Assessment and labelling of Textile Floorcovering tested to BS4730 (Hot Metal Nut Test) - Low Radius of Char</td> </tr> <tr> <td>BS EN 13501</td> <td>Class Bfl-s1</td> </tr> <tr> <td>Castor Chair Test</td> <td>Suitable for intensive use with castor chairs</td> </tr> <tr> <td>Warranty</td> <td>10 years</td> </tr> <tr> <td>VOC Content</td> <td>E1 in relation to EN 14041:2004</td> </tr> <tr> <td>Environmental Status</td> <td>BREEAM® A Rated</td> </tr> </table>	Style	Tufted 1/10" Gauge Loop Pile Tile	Yarn Construction	100% Solution Dyed Nylon	Pile Yarn Weight	500gsm	Pile Height	3mm	Total Weight	4280gsm	Total Thickness	5.5mm	Backing	100% Envirobac - minimum of 75% recycled material	Additional Backing	Komfort Bac available on request	Tile Size	50cm x 50cm	Tiles Per Box	20 (5m ²)	Wear Classification	Heavy Contract Class 33	Luxury Class	LC1	Anti-static	Suitable for use with computers. Less than 2Kv	Colour Fastness	Light (BS EN ISO 105:B02) >6 Shampoo (BS 1006:UK-TB:1990) 4-5 Dry Rubbing (BS EN ISO 105:B01) 4-5 Wet Rubbing (BS EN ISO 105:X12) 4-5	Flammability	BS5287 Assessment and labelling of Textile Floorcovering tested to BS4730 (Hot Metal Nut Test) - Low Radius of Char	BS EN 13501	Class Bfl-s1	Castor Chair Test	Suitable for intensive use with castor chairs	Warranty	10 years	VOC Content	E1 in relation to EN 14041:2004	Environmental Status	BREEAM® A Rated
	Style		Tufted 1/10" Gauge Loop Pile Tile																																									
	Yarn Construction	100% Solution Dyed Nylon																																										
	Pile Yarn Weight	500gsm																																										
Pile Height	3mm																																											
Total Weight	4280gsm																																											
Total Thickness	5.5mm																																											
Backing	100% Envirobac - minimum of 75% recycled material																																											
Additional Backing	Komfort Bac available on request																																											
Tile Size	50cm x 50cm																																											
Tiles Per Box	20 (5m ²)																																											
Wear Classification	Heavy Contract Class 33																																											
Luxury Class	LC1																																											
Anti-static	Suitable for use with computers. Less than 2Kv																																											
Colour Fastness	Light (BS EN ISO 105:B02) >6 Shampoo (BS 1006:UK-TB:1990) 4-5 Dry Rubbing (BS EN ISO 105:B01) 4-5 Wet Rubbing (BS EN ISO 105:X12) 4-5																																											
Flammability	BS5287 Assessment and labelling of Textile Floorcovering tested to BS4730 (Hot Metal Nut Test) - Low Radius of Char																																											
BS EN 13501	Class Bfl-s1																																											
Castor Chair Test	Suitable for intensive use with castor chairs																																											
Warranty	10 years																																											
VOC Content	E1 in relation to EN 14041:2004																																											
Environmental Status	BREEAM® A Rated																																											
	Foundry Grey, 810 (LRV - 6.63)		Mouse, 830 (LRV - 16.28)																																									
	London Stone, 820 (LRV - 10.04)			Denim, 616 (LRV - 4.95)																																								
	Liberty, 612 (LRV - 3.13)			Electric, 625 (LRV - 5.12)																																								
	Racing Green, 505 (LRV - 4.89)			Skylight, 640 (LRV - 7.65)																																								
		Razzmic Berry, 740 (LRV - 6.07)			Grasshopper, 550 (LRV - 14.41)																																							
		Blazer, 210 (LRV - 4.52)			Purple Rain, 750 (LRV - 4.26)																																							
		Bark, 108 (LRV - 9.82)			Bark, 108 (LRV - 9.82)																																							

TOTAL COLOURWAY OPTIONS - 15

BROADLOOM DESIGN

TESSELLATED DESIGN

AVAILABLE FROM STOCK

MADE IN BRITAIN

Tile colours representative in print, order a full tile for true likeness.